



/ 스팀용 - 180°C미만 /

규격 Dia.(DN)	재질 (Mat'l)	내관			외관(HDPE)			보온재				단위중량 (kg/m)	길이 (M)
		외경 (D)	두께(T)	단위중량 (kg/m)	외경 (D)	두께 (T)	단위중량 (kg/m)	Perlite		Polyurethane Foam			
								두께 (T)	단위중량 (kg/m)	두께 (T)	단위중량 (kg/m)		
20A		27.2	2.9	1.74	160	3.2	1.51	30	0.14	33.20	1.48	4.87	
25A		34.0	3.4	2.57	160	3.2	1.51	30	0.18	29.80	1.48	5.72	
32A		42.7	3.6	3.48	200	3.5	2.06	30	0.22	45.15	2.30	8.06	
40A		48.6	3.7	4.10	200	3.5	2.06	30	0.25	42.20	2.27	8.68	
50A		60.5	3.9	5.45	200	3.5	2.06	40	0.42	26.25	2.18	10.11	
65A		76.3	5.2	9.12	225	3.5	2.32	40	0.53	30.85	2.71	14.68	
80A		89.1	5.5	11.34	250	4.0	2.95	40	0.62	36.45	3.30	18.21	
100A		114.3	6.0	16.03	250	4.0	2.95	40	0.79	23.85	2.96	22.73	
125A	SPPS 380E	139.8	6.6	21.68	315	5.6	5.19	40	0.97	42.00	4.74	32.58	6,000
150A		165.2	7.0	27.69	315	5.6	5.19	40	1.14	29.30	4.23	38.25	
200A		216.3	8.2	42.09	400	6.3	7.43	40	1.49	45.55	6.73	57.74	
250A		267.4	9.3	59.20	450	7.8	1.33	40	1.85	43.50	7.64	79.02	
300A		318.5	10.3	78.29	500	7.8	11.49	50	2.75	32.95	8.68	101.21	
350A		355.6	11.1	94.30	560	9.8	16.14	50	3.07	42.40	1.79	124.30	
400A		406.4	12.7	123.30	630	9.8	18.19	60	4.21	42.00	13.52	159.22	
450A		457.2	14.3	156.19	710	11.5	24.04	60	4.74	54.90	17.14	202.11	
500A		508.0	15.1	183.54	800	12.5	29.46	70	6.14	63.50	22.33	241.47	

※ 호칭은 내관 호칭기준
 ※ 수요자의 요구에 따라 사양 변경 가능

