



/ 상수도용 이중보온관 (신 KS PE수도관) /

관경	내관(PE)			외관(AL-Spiral / HDPE)				비고
	재질(Mat'l)	외경(mm)	두께(T)	AL-Spiral		HDPE		
				외관경(mm)	보온두께(T)	외관경(mm)	보온두께(T)	
20A	KSM3408-2	20.00	2.00	90.00	34.40	90.00	32.50	
25A	KSM3408-2	25.00	2.30	90.00	31.90	90.00	30.00	
32A	KSM3408-2	32.00	3.00	90.00	28.40	90.00	26.50	
40A	KSM3408-2	40.00	3.70	110.00	34.40	110.00	32.00	
50A	KSM3408-2	50.00	4.60	110.00	29.40	110.00	27.00	
63A	KSM3408-2	63.00	5.80	125.00	30.40	125.00	27.80	
75A	KSM3408-2	75.00	6.80	140.00	31.90	140.00	29.30	
90A	KSM3408-2	90.00	8.20	160.00	34.20	160.00	31.80	
110A	KSM3408-2	110.00	10.00	200.00	44.00	200.00	41.50	
125A	KSM3408-2	125.00	11.40	225.00	49.00	225.00	46.50	
140A	KSM3408-2	140.00	12.70	225.00	41.50	225.00	39.00	
160A	KSM3408-2	160.00	14.60	250.00	44.00	250.00	41.00	
180A	KSM3408-2	180.00	16.40	315.00	66.50	315.00	61.90	
200A	KSM3408-2	200.00	18.20	315.00	56.50	315.00	51.90	
225A	KSM3408-2	225.00	20.50	315.00	44.00	315.00	39.40	
250A	KSM3408-2	250.00	22.70	400.00	74.00	400.00	68.70	
280A	KSM3408-2	280.00	25.40	450.00	83.80	450.00	77.20	
315A	KSM3408-2	315.00	28.60	450.00	66.30	450.00	59.70	

내외관은 용도와 주문자 사양에 따라 변경 가능(내관 종류 : 동관, SUS관, 도복장 강관, 주철관, 주름관 등)

